

Item # CT4440, High Pressure Tee Fittings

QUOTE

High Pressure Tee Fittings


All Autoclave Engineers valves and fittings are supplied complete with appropriate glands and collars. To order these components separately, use order numbers listed. When using plug, collar is not required.

To ensure proper fit use Autoclave Engineers tubing.

All dimensions for reference only and subject to change. For prompt service, Autoclave stocks select products. Consult your local representative.

Fittings such as 45° elbows, reducer elbows, and reducer 45° elbows are available upon request. For mounting hole option add suffix PM to catalog number, consult factory for mounting hole dimensions. Contact your local sales representative for additional information.

All general terms and conditions of sale, including limitations of our liability, apply to all products and services sold.



SPECIFICATIONS

| | |
|-----------------------|--------------------------|
| Connection Type | F250C |
| Outside Diameter Tube | 1/4 Inch 6.35 mm |
| Pressure Rating | 60000 psi 4136.79 bar |
| Minimum Opening | 0.094 Inch 2.39 mm |
| A - Height | 1.25 Inch 31.75 mm |
| B - Width | 2 Inch 50.8 mm |
| C - Height | 0.50 Inch 12.70 mm |
| D - Typical Hex | 0.63 Inch 15.88 mm |
| E - Length | 0.88 Inch 22.35 mm |
| F - Length | 1.00 Inch 25.40 mm |

Block Thickness

1.00 Inch
25.40 mm